



INTERNATIONAL SAFETY EQUIPMENT, INC.
 Post Office Box 585 - Devault, PA. 19432-0585 U. S. A.
 Voice: 610. 935. 8866
 f. 610. 590. 0108 – e. Sales@System99.com - w. www.System99.Com



SYSTEM *99* STOCK # 1220-SS ANSI CLASS III ~ WORK POSITIONING ~ SEAT HARNESS ~ PUT-ON-INSTRUCTIONS



First: Make sure all straps are un-buckled - and are *twist-Free* ~ Place the shoulder straps on either side of your head. Make sure the back *D* ring on the back straps faces out ... (Do not tighten the straps length yet) ...

Second: Fasten the waist strap buckle around your waist - not too tight ... the waist strap is smaller in width than the *under the butt* strap ...

Third: Sort and install the leg straps ... also not too tight yet ...

Fourth: Adjust the butt strap as shown above ... It goes over the leg straps, and the waist belt. The D-Ring ends of the butt strap are brought together by the lower Karabiner of the *99* system. Once you've positioned the butt strap, adjust the shoulder straps, attach the short black strap at near sternum level, the leg straps, & the waist strap to be quite snug ... not so tight as to be binding or uncomfortable ... but tight, just the same ...

[HINT] - You can adjust the butt / seat / strap slightly up or down ... but be careful ... too much up or down might have a tendency to pitch you too far forward or back ... you want yourself supported in a sitting position without having to hold yourself in that position by grabbing the suspension ropes ...

PLEASE: CALL US IF YOU HAVE ANY PROBLEMS OR QUESTIONS ... 610. 935. 8866 ...