



**INTERNATIONAL SAFETY EQUIPMENT, INC.**  
Post Office Box 585 - Devault, PA. 19432-0585 U. S. A.  
Voice: 610. 935. 8866  
f. 610. 590. 0108 – e. [Sales@System99.com](mailto:Sales@System99.com) - w. [www.System99.Com](http://www.System99.Com)



**SYSTEM \*99\* ~ SKYE CHAIR HANDLE SECURING ROPE HALVING INSTRUCTIONS**



**\*Halving\* the handle securing rope, [see left], keeps the handle in close proximity to the Skye Chair / or harnessed worker, and within easy reach. In addition, as the occupant of the Chair is limited to about two feet of upward handle slide reach when doing self-lifting this is a more convenient way of tying off the handle.**

**To \*halve\* the handle securing rope when using any of our Skye Chairs [or] any of our harnesses:**

**Remove the karabiner from the non-handle end of the four (4) foot handle securing rope thimble eye. Pass this thimble eye through one of the \*D\* rings that are found on either side of the Chair seat / or pass it through one of the secured harness straps. Next, ~ re-install the karabiner and attach the karabiner & securing line to the second hole in the bottom of the handle.**

**When ascending / & once you reach the spot where you wish to stop & work / slide the handle up the free-side rope the shortened distance until the handle securing rope is taught. At this point, you are tied off so you can let go of the handle and have both hands free for your work.**